

SIGNATURE: _____ DATE: _____

Pin 9,10,47~50 re-defined
LCD V.A changed

15-4-16



1. DISPLAY TYPE:	2.6"IPS_LCD /TRANSMISSIVE
2. LCD OPERATING VOLTAGE:	2.8-3.3V
3. OPERATING TEMPERATURE:	-20°C~70°C
4. STORAGE TEMPERATURE:	-30°C~80°C
5. VIEWING ANGLE:	ALL
6. DRIVE MODE:	1/320DUTY
7. DRIVER:	ILI9341
8. RESOLUTION:	240(RGB)X320
9. BACKLIGHT:	6 WHITE LED,120MA,3.2±0.3V
10. CONNECTOR:	FPC

No	PIN NAME
1	GND
2	VCC
3	VCC
4	IM2
5	IM1
6	IM0
7	RESET
8	CS
9	DC/SCL
10	WR/DC
11	RD
12	YSYNC
13	HSYNC
14	ENABLE
15	DOTCLK
16	SDA
17	DB0
18	DB1
19	DB2
20	DB3
21	DB4
22	DB5
23	DB6
24	DB7
25	DB8
26	DB9
27	DB10
28	DB11
29	DB12
30	DB13
31	DB14
32	DB15
33	DB16
34	DB17
35	SIO0
36	LEDA
37	LEDPK1
38	LEDPK2
39	LEDPK3
40	LEDPK4
41	LEDPK5
42	LEDPK6
43	XR(-)
44	Y1(V+)
45	XL(X-)
46	Y0(V-)
47	GND
48	GND
49	GND
50	GND

 MACLIGHT DISPLAY CO., LIMITED

GENERAL TOL	ALL UNITS:	DATE		SHEET: 1 OF 1
0.20	MM			
DWN:				
CHK:				
APP:			DO NOT SCALE THIS DRAWING.	DATE:
			PROJECTION	

特殊工艺: